



**SR 3002 SUPERELEVATION**

**LEFT SIDE**  
 STA 36+70.00 TO STA 37+20.00: SE VARIES FROM 2.41% (EXISTING) TO 3.97%  
 STA 37+20.00 TO STA 38+42.76: SE IS 3.97%  
 STA 38+42.76 TO STA 39+55.00: SE VARIES FROM 3.97% TO -2.0%  
 STA 39+55.00 TO STA 41+51.00: SE IS -2.0%  
 STA 41+51.00 TO STA 42+26.20: SE VARIES FROM -2.0% TO 2.0%  
 STA 42+26.20 TO STA 43+20.00: SE IS 2.0%  
 STA 43+20.00 TO STA 43+90.00: SE VARIES FROM 2.0% TO -1.7% (EXISTING)

**RIGHT SIDE**  
 STA 36+70.00 TO STA 37+20.00: SE VARIES FROM -3.03% (EXISTING) TO -3.97%  
 STA 37+20.00 TO STA 38+42.76: SE IS -3.97%  
 STA 38+42.76 TO STA 38+79.80: SE VARIES FROM -3.97% TO -2.0%  
 STA 38+79.80 TO STA 43+20.00: SE IS -2.0%  
 STA 43+20.00 TO STA 43+90.00: SE VARIES FROM -2.0% TO -2.26% (EXISTING)

**LEGEND**

--- SEEDING AND SOIL SUPPLEMENTS - FORMULA L CLEAR ZONE MIX OR FORMULA B RESIDENTIAL MIX

① SUPERPAVE ASPHALT MIXTURE DESIGN, WEARING COURSE  
PG 64-22, < 0.3 MILLION ESALS, 12.5 MM MIX, 2" DEPTH, SRL-L

② SUPERPAVE ASPHALT MIXTURE DESIGN, BASE COURSE  
PG 64-22, < 0.3 MILLION ESALS, 25.0 MM MIX, 5" DEPTH

③ SUBBASE, 6" DEPTH (NO. 2A)

④ GEOTEXTILE, CLASS 4, TYPE A

NOTE: APPLY ASPHALT TACK COAT BETWEEN ALL PAVEMENT LAYERS.

- LANES
- SHOULDERS
- DRIVEWAY ADJUSTMENT
- STREAM/CHANNEL
- WETLANDS



